

WIDE HEAD



POLECAM

Specially designed for D-SLR Cameras this head benefits from full electronic control with pulse encoded Faulhaber motors used for both pan and tilt operations.

The head uses a 12 bit PID motion controller to regulate the pan and tilt axis via a closed loop configuration meaning you get an extremely accurate and easily controllable head. This head can move up to 30 times slower than previous versions and can also do a full 360° in just 7 seconds.

The Wide head is backwards compatible with most Polecam rigs.

Weight: 1394g / 3.07lb(US)
Max payload: 3.6Kg / 8lb

Overall height (pivot to base):
500mm/19.6"

Max load height on cradle:
240mm / 9.45"
Max load width on cradle:
200mm / 7.87"

Base plate:
100mm / 3.94" depth
slotted centre with two
additional slots either side at
20mm / 0.78" intervals, slot
width is 6.5mm / 0.255"



Polecam Ltd
12 Wolseley Road
Woburn Road Industrial Estate
Kempston, Bedfordshire
MK42 7TN, UK

+44 (0)1234 855 222

+44 (0)1234 855 270

sales@polecam.com

www.polecam.com

POLECAM



The Wide Head is designed with flexibility in mind and you can detach the Polecam mounting bracket drop arm (4 screws) and that will reveal a 3/8 UNC thread tapped into the plate on the top of the Wide Head. Attach the inverted head to whatever suits your intended use.

The Wide Head is great for 3D with two mini cams side by side using our optional 3D mounting plate.

Due to the load capacity and the ability to re position the mounting cradle the Wide Head can potentially take a wide variety of cameras.

